

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 August 2002 (22.08.2002)

PCT

(10) International Publication Number
WO 02/065009 A2

- (51) International Patent Classification⁷: F16L (81) Designated State (*national*): US.
- (21) International Application Number: PCT/US02/03543 (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- (22) International Filing Date: 8 February 2002 (08.02.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2001-037098 14 February 2001 (14.02.2001) JP
- (71) Applicant (*for all designated States except US*):
EMHART LLC [US/US]; Drummand Plaza Office
Park, 1423 Kirkwood Highway, Newark, DE 19711 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): NAKANISHI,
Hideaki [JP/JP]; c/o Pop Rivet Fastener K.K., Hosoda,
Noyori-cho, Toyohashi-shi, Aichi-ken (JP).
- (74) Agents: BROCK, Christopher, M. et al.; Harness,
Dickey & Pierce, P.L.C., P.O. Box 828, Bloomfield Hills,
MI 48303 (US).
- Declarations under Rule 4.17:**
— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR)
— as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations of inventorship (Rule 4.17(iv)) for US only
- Published:**
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 02/065009 A2

(54) Title: FASTENER FOR PIPE OR THE LIKE

(57) Abstract: A fastener (21) for a pipe or the like, comprising a base (22) and a pipe holder portion (23-26) supported by the base. The pipe holder portion includes a wall (30, 31) defining a recess for receiving a pipe or the like therein, and a resilient holding finger (34) extending obliquely from the vicinity of the end of the wall into the recess. The pipe holder portion is supportably connected to the base (22) through a hollow tubular cushion portion (41). The end of the wall of the pipe holder portion is connected, through a short sheet-like thin connecting piece (43), to either an adjacent wall of another pipe holder portion or an adjacent wall integrated with the base. The thin connecting piece (43) is formed in a thin plate having the same length as that of the pipe holder portion in the longitudinal direction of the pipe. The thin connecting piece is formed with a slit (45) extending in the longitudinal direction of the pipe.

FASTENER FOR PIPE OR THE LIKE

FIELD OF THE INVENTION

The present invention relates to a fastener for holding an elongated component such as a pipe or wire harness to a member such as an automobile body.

5

BACKGROUND OF THE INVENTION

In a support structure for attaching an elongated component such as a fuel pipe, brake pipe or wire harness of an automobile, it is desired to have vibration absorbability for preventing vibration of an automobile body from transmitting to the above pipe or the like. Heretofore, for the purpose of such vibration insulation, a technique of attaching the pipe or the like to a fastener with winding a rubber vibration insulator around the pipe or the like has been typically employed. In view of a poor workability of this technique, it is desired to provide a vibration insulation function to the fastener itself. From this point of view, Japanese Patent Laid-Open No. 07-310866 discloses a clip fastener suitable for holding a fuel pipe, in which a pipe holder portion is connected to a support through a hollow portion. This clip is intended for supporting an elongated component such as a pipe, and designed to prevent vibration transmission from the pipe or the like to an automobile body or the like (or vibration transmission from the automobile body to the pipe or the like) as much as possible. In the disclosed clip fastener for a pipe or the like, a structure having four pipe holder portions arranged in line is disclosed as an embodiment. However, a significant difference in vibration insulation characteristics can be caused between the line center and the line ends of the pipe holder portion.

Japanese Patent Laid-Open No. 2000-18433 discloses a fastener for a pipe or the like, which has an improvement in the above point. Figs. 1 and 2 show this fastener. In Fig. 1, the fastener 1 comprising a base 2 and a pipe holder portion 3 supported by the base 2. The pipe holder portion 3 includes a curved wall 6 defining a recess 5 for receiving an elongated component such as a pipe therein, and a resilient holding finger 7 extending obliquely from the end of the curved wall 6 into the recess. The pipe holder portion 3 is supportedly connected to the base 2 through a hollow tubular cushion portion 9. The fastener 1 provides excellent vibration insulation characteristics between the base 2 and the pipe holder portion 3. Further, even if a plurality of retaining portions 3 are arranged in line, the fastener 1 desirably provides unnoticeably suppressed difference in vibration insulation characteristics between the respective retaining portions 3.

As shown in Figs. 1 and 2, in the fastener disclosed in the aforementioned Japanese Patent Laid-Open Publication No. 2000-18433, the end of the curved wall 6 of the pipe holder portion 3 is connected to the end of the adjacent curved wall 6 of another pipe holder portion 3 through a flexible V-shaped thin connecting piece 10.

5 The end of the curved wall 6 of the pipe holder portion 3 is also connected to the end of the adjacent wall 13 of the base through a flexible thin connecting piece 11 arranged obliquely. While these flexible thin connecting pieces 10 and 11 were desirable in terms of vibration insulation, it was found that there was the need to be improved in a fastening force of the pipe holder portion 3. This will be explained with

10 reference to Fig. 2 showing the portion designated by the circle 14 in Fig. 1. In Fig. 2, when a force of pushing out a pipe in the direction of the arrow 17 is applied to a pipe 15 held by the pipe holder portion 3, the thin connecting piece 10 is, for example, deformed from the angle "a" to the angle "b" in Fig. 2 because the thin connecting pieces 10 and 11 are flexible. Then, the curved wall 6 at the right side of Fig. 2 is

15 deformed rightward. Simultaneously, the thin connecting piece 11 is also deformed slightly, and thereby the curved wall 6 adjacent to the wall 13 is deformed leftward. As a result, the inlet of the curved wall 6 is widely opened, and the resilient holding finger 7 is displaced rightward with respect to the pipe 15. Thus, it was found that the pipe 15 could be pulled out of the pipe holder portion 3 due to insufficiently degraded

20 engagement force of the pipe 15.

It is therefore an object of the present invention to provide a fastener for holding an elongated component such as a pipe to an attachment member such as an automobile body, capable of maintaining a fastening force of the elongated component such as a pipe at high levels while maintaining insulating characteristics

25 against vibration transmitted from the pipe or the like to an automobile body or vice versa at high levels.

SUMMARY OF THE INVENTION

In order to achieve the above object, the present invention provides a fastener for a pipe or the like, comprising a base and a pipe holder portion supported

30 by the base. The pipe holder portion includes a wall defining a recess for receiving an elongated component such as a pipe therein, and a resilient holding finger extending obliquely from the end of the wall or the vicinity thereof into the recess. The pipe holder portion is supportedly connected to the base through a hollow tubular cushion portion. Further, the end of the wall of the pipe holder portion is connected to either

35 an adjacent wall of another pipe holder portion or an adjacent wall integrated with the

base through a sheet-like thin connecting piece. As above, since the pipe holder portion is connected to the base through the tubular cushion portion and the thin connection piece, vibration insulation characteristics between the pipe holder portion and the base can be maintained in high levels. Further, the end of the wall is
5 connected to the adjacent wall (or the wall of the base) through the short sheet-like thin connecting piece. Thus, even if a pushing-out force is applied to a held pipe to force the wall to be deformed in the direction causing the inlet to be opened, the thin connecting piece strains to resist the deformation. This prevents the wall from being deformed and allows the fastening force of the pipe to be maintained in high levels.

10 In a preferred embodiment of the present invention, a base of a fastener for a pipe or the like includes an elongated bottom portion and an upright portion extending perpendicularly from the opposite ends of the bottom portion, and a plurality of pipe holder portions are supported by the base to be arranged each other with a certain distance therebetween in the longitudinal direction of the base. Each of
15 the pipe holder portions includes a wall defining a recess for receiving an elongated component such as a pipe therein, and a resilient holding finger extending obliquely from the end of the wall or the vicinity thereof into the recess. Each of the pipe holder portions is supportedly connected to the base through a hollow tubular cushion portion. Further, in the pipe holder portion adjacent to the upright portion of the base
20 among the pipe holder portions, the end of the wall adjacent to the upright portion is connected to the upright portion by a short sheet-like thin connecting piece, and the opposite end of the wall is connected to the end of the wall of the adjacent pipe holder portion by a short sheet-like thin connecting piece.

In the aforementioned fasteners for a pipe or the like, the thin connecting
25 piece may be formed in a thin plate having the same length as that of the pipe holder portion in the longitudinal direction of the elongated component to be attached to the recess, and the thin connecting piece may be formed with a slit extending in the longitudinal direction of the component. This provides an improved, enhanced vibration insulation characteristics. The bottom portion of the base may be provided
30 on the opposite side of the pipe holder side with a coupling leg to be coupled with an attachment member. This allows an elongated component such as a pipe to be attached to an attachment member such as an automobile body. In addition, the base may be formed with an attaching portion to be attached to an anchor member such as a stud fixed to an attachment member. This allows an elongated component
35 such as a pipe to be attached to an attachment member such as an automobile body.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a front view of the state when a conventional pipe fastener (Japanese Patent Laid-Open No. 2000-18433) is used.

Fig. 2 is an enlarged view of a portion designated by the circle 14 of Fig. 1.

5 Fig. 3 is a front view of a fastener for a pipe or the like according to the present invention.

Fig. 4 is a plan view of the fastener of Fig. 3.

Fig. 5 is a plan view of the fastener showing the state when a pipe is held by the pipe fastener according to the present invention.

10 Fig. 6 is a front view of the fastener of Fig. 5.

Fig. 7 is an enlarged explanatory view illustrating the left side portion of Fig. 6 and showing the relationship of forces caused when pulling-out force is applied to a single pipe.

15 Fig. 8 is an enlarged explanatory view illustrating the left side portion of Fig. 6 and showing the relationship of forces caused when pulling-out force is applied to two adjacent pipes, simultaneously.

Fig. 9 is a front view showing a fastener for pipe or the like according to one embodiment of the present invention, in which the fastener is attached to an automobile body.

20 Fig. 10 is a front view showing a fastener for pipe or the like according to another embodiment of the present invention, in which the fastener is attached to an automobile body.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

25 With reference to the drawings, an embodiment of the present invention will now be described. Figs. 3 and 4 show a construction of a fastener 21 for a pipe or the like according to the present invention. Figs. 5 and 6 show the fastener 21 in the state when pipes are held thereby. Figs. 7 and 8 illustrate a fastening force of a pipe in the fastener 21. Figs. 9 and 10 show an example of attaching a pipe as an elongated component to an automobile body as an attachment member by using the
30 fastener 21. The fastener 21 according to the present invention is an integrally formed product made of a plastic material. As shown in Figs. 3 and 4, the fastener 21 comprises a base 22 and a plurality (four in the illustrated embodiment) of pipe holder portions 23-26 supported by the base 22. The base 22 includes an elongated bottom portion 28 and upright portions 29 extending perpendicularly from opposite
35 ends of the bottom portion 28. The pipe holder portions 23-26 are aligned in the

longitudinal direction of the elongated bottom portion 28 of the base 22. Each of the outer pipe holder portions 23 and 26 is formed to hold a larger-diameter pipe, and each of the inner pipe holder portions 24 and 25 is formed to hold a smaller-diameter pipe.

5 In Fig. 3, each of the pipe holder portions 23-26 includes a main holder portion 30 forming a bottom wall having an approximately semicircular section and an upright wall 31 extending perpendicularly upward from each of the edges of the main holder portion 30, and defines therein a recess for receiving or housing an elongated component such as a pipe or the like. An inward holding-protrusion 33 is formed at
10 each of the inner sides of two boundaries between the main holder portion 30 and the upright walls 31. At each outer end of the upright walls 31 is formed with a resilient holding finger 34 extending obliquely inward. As shown in Fig. 6, each of the pipes 36-39 is received in the corresponding one of the pipe holder portions 23-26 to allow the lower and both lateral sides of each outer peripheral surface of the pipes to
15 be brought into contact with the central upper surface and the protrusions 33 of the corresponding main holder portion 30, respectively. Further, the upper side of each outer peripheral surface of the pipes is pushed downward by the two resilient holding fingers 34 to allow each of the pipes to be held by the corresponding one of the pipe holder portions 23-26.

20 Further, a hollow tubular cushion portion 41 is formed on the outer and lower surface of the main holder portion 30 of each of the pipe holder portions 23-26. The lower surface of the cushion portion 41 is connected to the bottom portion 28 of the base 22 through a support post 42. In this manner, each of the pipe holder portions 23-26 is supported by the base 22 through the hollow tubular cushion portion 41.
25 Thus, the cushion portion 41 brings out a cushioning action against vertical vibrations, and substantially no vibration of the pipe is transmitted from the cushion portion 41 to the base 22. Thus, the cushion portion 41 can act as vibration insulation means.

As best shown in Figs. 3 and 4, the adjacent two pipe holder portions 23 and
30 24, 24 and 25, 25 and 26 are connected with each other at the adjacent ends of their upright walls through a short sheet-like thin connecting piece 43. The thin connecting piece 43 is formed in a plate configuration, and is hardly deformed. Further, the pipe holder portion 23 and the upright portion 29 (i.e. the wall) of the base 22 adjacent to this pipe holder portion 23 are connected with each other through the short sheet-like
35 thin connecting piece 43. In the same manner, the pipe holder portion 26 and the

upright portion 29 adjacent to this pipe holder portion 26 are connected with each other through the short sheet-like thin connecting piece 43. Each of the sheet-like thin connecting pieces 43 is formed in a thin plate having the same length as that of the pipe holder portion in the longitudinal direction of the pipe. As above, the connecting piece 43 is formed to have a thin thickness. This reduces lateral vibration transmission between the adjacent pipe holder portions and another lateral vibration transmission between the upright portion 29 of the base 22 and the pipe holder portion 23 or 26. The thin connecting piece 43 can sufficiently resist against a pulling-out force applied from both ends of the thin connecting piece 43, and can strain against a pushing force applied in the opposite direction without any bending to resist against any pressing forces. Thus, even if a pulling-out force is applied to the pipe to create a force which deforms the upright wall 31 of the pipe holder portion toward the adjacent upright wall of the neighbor pipe holder portion, the thin connecting piece 43 strains on the basis of the adjacent upright wall 31 of the neighbor pipe holder portion and thereby the upright wall 31 having the pipe applied with the pulling-out force is not deformed. This allows the fastening force of the pipe to be maintained in high levels.

Each of the thin connecting pieces 43 is also formed with a slit 45 (see Fig. 4) extending in the longitudinal direction of the pipe. The slit 45 is formed at the center of the thin connecting piece 43 based on the longitudinal direction of the pipe, and each of the thin connecting pieces 43 connects the pipe holder portions 23-26 and the upright portions 29 at the opposite ends of the slit 45. By forming this slit, the lateral vibration transmission between respective the pipe holder portions is further reduced, and the lateral vibration transmission between the upright portions 29 of the base 22 and the pipe holder portions 23-26 is further reduced. The size of the slit 45 can be formed to allow the straining force of the thin connecting piece 43 to be maintained.

An engagement leg 46 having a conventional anchor-type resilient engagement pawl is provided at the center of the lower surface in the longitudinal direction of the bottom portion 28 of the base 22. The fastener 21 can be attached to an automobile body or the like by inserting the engagement leg 46 into a mounting hole of the automobile body, a bracket fixed to an automobile body or the like,

Figs. 5 and 6 show the state when pipes 36-39 are held by the fastener 21. Generally speaking, where a fuel pipe, brake oil pipe, or a pipe such as a wire harness is attached to an automobile, the fastener 21 is practically delivered to a

manufacturer of the fuel pipe, the wire harness or the like. Then, the fastener 21 is attached in a plurality of predetermined positions to hold a plurality of pipes under a predetermined schematic design. Thereafter, a plurality of pipes such as a fuel pipe or wire harness, to which the plurality of fasteners are attached under the predetermined design, are delivered to an automobile manufacturer, and are attached to predetermined positions of an automobile body by using the fastener 21 or the like. Thus, the state when the pipes 36-39 are held by the fastener 21 as shown in Figs. 5 and 6 corresponds to the state when it is carried to the automobile manufacturer. For example, if the pipes are carried in the above state, a force acting to pull the pipes 36-39 out of the fastener 21 can be applied. In the conventional fastener 1, the pipe 15 can come off as explained with reference to Fig. 2. However, in the fastener 21 according to the present invention, even if a force acting to pull the pipes 36-39 out of the fastener 21 is applied, the pipes does not come off. This reason will be described with reference to Figs. 7 and 8.

Fig. 7 shows the state when a pulling-out force is applied to one pipe 36 in the direction of the arrow Y. In this case, the pulling-out force Y of the pipe 36 applies a force Y1 to the pair of resilient holding fingers 34, and applies a force Y2 to the pair of thin connecting pieces 43. The thin connecting pieces 43 are thin, but not deformed. Thus, the left-side thin connecting piece 43 applies the force Y2 as-it to the upright portion 29 of the base. The upright portion 29 receives this force without its deformation because of its high rigidity. In this state, while the force Y2 itself and a reaction force Y2 from the upright portion 29 act on the thin connecting piece 43, the thin connecting piece 43 is not deformed because of its anti-bendability and strains resistively against these forces. Thus, the left-side resilient holding finger 34 is maintained in a posture for engaging the pipe 36 even if the force Y1 acts thereon. On the other hand, the right-side thin connecting piece 43 connected to the upright wall 31 of the neighbor pipe holder portion 24 applies the force Y2 as a force Y3 to the resilient holding finger 34. While this force acts on the pipe 37 held by the pipe holder portion 24, the pipe 37 receives the force without its deformation because of its high rigidity. The force Y2 itself and a reaction force from the pipe 37 and the resilient holding finger 34 act on the thin connecting piece 43. However, the thin connecting piece 43 resistively strains so as not to be deformed. Thus, the right-side resilient holding finger 34 is also maintained in a posture for engaging the pipe 36 even if the force Y1 caused by the pulling-out force Y acts thereon. In this manner,

even if the pulling-out force is applied to one pipe, the inlet of the pipe holder portion is not opened, and thereby the pipe does not come off.

Fig. 8 shows the state when a pulling-out force is applied to the two adjacent pipes 36 and 37 in the direction of the arrows Ya and Yb. In this case, the pulling-out force Ya of one pipe 36 applies a force Ya1 to the pair of resilient holding fingers 34 and applies a force Ya2 to the pair of thin connecting pieces 43. As described in Fig. 7, the upright portion 29 receives the force without its deformation because of its high rigidity, and the force Y2 itself and the reaction force from the upright portion 29 each having the same magnitude act on the thin connecting piece 43. However, the thin connecting piece 43 resistively strains these forces without its deformation. Thus, even if the force Y1 is applied to the left side resilient holding finger 34, the left side resilient holding finger 34 is maintained in a posture for engaging the pipe 36. On the other hand, the force Ya2 is applied to the right-side thin connecting piece 43 connected to the upright wall 31 of the neighbor pipe holder portion 24. The pulling-out force Yb of the other pipe 37 applies a force Yb1 to the pair of resilient holding fingers 34, and applies a force Yb2 to the pair of thin connecting pieces 43. Thus, the force Ya2 from the right-side resilient holding finger 34 of the pipe holder portion 23 and the force Yb2 from the left-side resilient holding finger 34 of the pipe holder portion 24 act on the thin connecting piece 43 connecting between the pipe holder portions 23 and 24. However, the thin connecting piece 43 resists so as not to be deformed. Thus, the right-side resilient holding finger 34 of the pipe holder portion 23 and the left side resilient holding finger 34 of the pipe holder portion 24 are maintained in each posture for engaging the pipes 36 and 37. Further, the force Yb1 of the right-side resilient holding finger 34 of the pipe holder portion 24 applies the force Yb2 to the thin connecting piece 43 on the right side of the right-side resilient holding finger 34. However, even if the force Yb1 caused by the pulling-out force Yb is applied to the right-side resilient holding finger 34, for the same reason as that in the right-side thin connecting piece 43 of the pipe holder portion 23 in Fig. 7, the right-side resilient holding finger 34 is maintained in a posture for engaging the pipes 37. In this manner, even if a pulling-out force is applied to the two adjacent pipes, each inlet of the pipe holder portions are not be opened, and the pipe does not come out.

Fig. 9 shows an example of attaching the fastener 21 to an automobile body 47. The fastener 21 is attached to a mounting bracket 49 by inserting an engagement leg 46 into a hole formed in the mounting bracket 49. The one end of the mounting

bracket 49 is attached to an automobile body 47 with a bolt 51 and a nut 53 through an elastic bush 50, and thereby the pipes 36-39 are held by the automobile body 47. Thus, no vibration is transmitted from the pipes to the automobile body 47, and no vibration is transmitted from the automobile body 47 to the pipes 36-39. Further, even
5 if a pulling-out force is applied to an attached pipe, the pipes do not come off, and a high fastening force is maintained.

Fig. 10 shows another embodiment according to the present invention. Elements or components corresponding to the aforementioned embodiment are represented by the same reference numerals, and their detailed description will be
10 omitted. In this embodiment, individual structures of pipe holder portions 23-26 are the same as those in the embodiment shown in Figs. 3 and 4. The pipe holder portions 23-26 are supported to the base 22 through the hollow tubular cushion portion 41. The pipe holder portions 23-26 are connected with each other through the sheet-like thin connecting pieces 43, and the pipe holder portion 23 is connected to
15 the upright portion 29 of the base 22 through the thin connecting piece 43. The slit 45 shown in Fig. 4 is formed in each of the thin connecting pieces 43.

Instead of the wall-shaped upright portion, a stud-mounting portion 54 is formed to extend vertically upward at one of the opposite ends of the elongated bottom portion 28 of the base 22. The stud-mounting portion 54 has a rectangular
20 block-like shape and includes a through hole 55 in the longitudinal direction therewithin. Two pairs of engagement pawls 57 and 58 extending into the through hole 55 are formed in the stud-mounting portion 54. An automobile body 47A is provided with a stud 59 standing thereon. When the fastener 21 is pressed to the automobile body 47 to allow the stud 59 to be received in the through hole 55 of the
25 stud-mounting portion 54, the two paired engagement pawls 57 and 58 are engaged with the threads of the stud. Thus, the fastener 21 is fixed to the automobile body 47, and the pipes 36-39 are held by the automobile body 47. In this case, no vibration is also transmitted from the pipes to the automobile body, no vibration is transmitted from the automobile body to the pipes. Further, even if a pulling-out force is applied
30 to an attached pipe, the pipes do not come off and a high fastening force is maintained.

According to the present invention, the pipe holder portion is connected to the base through both the tubular cushion portion and the thin connection piece, so that
35 vibration insulation characteristics between the pipe holder portion and the base can

- be maintained in high levels. Further, the end of the wall is connected to the adjacent wall (or the wall of the base) through the short sheet-like thin connecting piece, whereby, even if a pushing-out force is applied to a held pipe and thereby the wall is urged to deform in the direction allowing the inlet to be opened, the thin connecting
- 5 piece strains to resist the deformation. This prevents the wall from being deformed and allows the fastening force of the pipe to be maintained in high levels.

CLAIMS

I claim:

1. A fastener for a pipe or the like, comprising a base and a pipe holder portion supported by said base, wherein said pipe holder portion includes a wall defining a recess for receiving an elongated component such as a pipe therein, and a resilient holding finger extending obliquely from the end of said wall or the vicinity thereof into said recess, and said pipe holder portion is supportedly connected to said base through a hollow tubular cushion portion, characterized in that the end of said wall of said pipe holder portion is connected, by a sheet-like thin connecting piece, to either an adjacent wall of another pipe holder portion or an adjacent wall which is integrated with said base.
2. A fastener for a pipe or the like, comprising:
 - a base including an elongated bottom portion and upright portions extending perpendicularly from the opposite ends of said bottom portion; and
 - a plurality of pipe holder portions supported by said base to be arranged each other with a certain distance therebetween in the longitudinal direction of said base, each of said pipe holder portions including a wall defining a recess for receiving an elongated component such as a pipe therein, and a resilient holding finger extending obliquely from the end of said wall or the vicinity thereof into said recess, and each of said pipe holder portions is supportedly connected to said base through a hollow tubular cushion portion; and
 - wherein in the pipe holder portion adjacent to said upright portion of said base among said pipe holder portions, the end of said wall adjacent to said upright portion is connected to said upright portion by a short sheet-like thin connecting piece, and the opposite end of said wall is connected to the end of the wall of the adjacent pipe holder portion by a short sheet-like thin connecting piece.
3. A fastener as defined in claim 1, wherein said thin connecting piece is formed in a thin plate having the same length as that of said pipe holder portion in the longitudinal direction of said elongated component to be attached to said recess, wherein said thin connecting piece is formed with a slit extending in the longitudinal direction of said component.
4. A fastener as defined in claim 2, wherein said bottom portion of said base is provided on the opposite side of the pipe holder side with a coupling leg to be coupled with an attachment member.

5. A fastener as defined in claim 1, wherein said base is formed with an attaching portion to be attached to an anchor member such as a stud which is fixed to an attachment member.

5 6. A fastener as defined in claim 2, wherein said thin connecting piece is formed in a thin plate having the same length as that of said pipe holder portion in the longitudinal direction of said elongated component to be attached to said recess, wherein said thin connecting piece is formed with a slit extending in the longitudinal direction of said component.

10 7. A fastener as defined in claim 3, wherein said base is formed with an attaching portion to be attached to an anchor member such as a stud which is fixed to an attachment member.

8. A fastener as defined in claim 6, wherein said base is formed with an attaching portion to be attached to an anchor member such as a stud which is fixed to an attachment member.

FIG. 1
(PRIOR ART)




FIG. 2
(PRIOR ART)




FIG. 3




FIG. 4




FIG. 5





FIG. 6



7/9

FIG. 7




FIG. 8






FIG. 9



9/9

FIG. 10



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
22 August 2002 (22.08.2002)

PCT

(10) International Publication Number
WO 02/065009 A3

- (51) International Patent Classification⁷: **F16L 3/223** (81) Designated State (national): US.
- (21) International Application Number: **PCT/US02/03543** (84) Designated States (regional): European patent (AT, BR, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- (22) International Filing Date: 8 February 2002 (08.02.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2001-037098 14 February 2001 (14.02.2001) JP
- (71) Applicant (for all designated States except US):
EMHART LLC [US/US]; Drummand Plaza Office
Park, 1423 Kirkwood Highway, Newark, DE 19711 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **NAKANISHI, Hideaki** [JP/JP]; c/o Pop Rivet Fastener K.K., Hosoda, Noyori-cho, Toyohashi-shi, Aichi-ken (JP).
- (74) Agents: **BROCK, Christopher, M.** et al.; Harness, Dickey & Pierce, P.L.C., P.O. Box 828, Bloomfield Hills, MI 48303 (US).
- Declarations under Rule 4.17:**
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR)
 - as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations of inventorship (Rule 4.17(iv)) for US only
- Published:**
- with international search report
- (88) Date of publication of the international search report:
27 February 2003
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FASTENER FOR PIPE OR THE LIKE



(57) Abstract: A fastener (21) for a pipe or the like, comprising a base (22) and a pipe holder portion (23-26) supported by the base (22). The pipe holder portion includes a wall (30, 31) defining a recess for receiving a pipe or the like therein, and a resilient holding finger (34) extending obliquely from the vicinity of the end of the wall into the recess. The pipe holder portion is supportably connected to the base (22) through a hollow tubular cushion portion (41). The end of the wall (31) of the pipe holder portion (23-26) is connected, through a short sheet-like thin connecting piece (43), to either an adjacent wall (31) of another pipe holder portion or an adjacent wall (29) integrated with the base (22). The thin connecting piece (43) is formed in a thin plate having the same length as that of the pipe holder portion in the longitudinal direction of the pipe. The thin connecting piece is formed with a slit (45) extending in the longitudinal direction of the pipe.

WO 02/065009 A3

PCT/US 02/03543

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 F16L3/223

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 F16L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 299 11 639 U (EMHART INC) 23 September 1999 (1999-09-23) cited in the application	1, 2, 4, 5
A	page 2, line 23 - line 28 page 4, line 19 - page 7, line 26 figures 1, 2	3, 6-8
A	EP 0 569 297 A (RAPID SA) 10 November 1993 (1993-11-10) figures	1-3, 5-8
A	EP 0 666 628 A (EMHART INC) 9 August 1995 (1995-08-09) cited in the application figures	1, 2, 4, 5

☒ Further documents are listed in the continuation of box C.

Y Patent family members are listed in annex.

- **Special categories of cited documents :**

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

2 September 2002

Date of mailing of the international search report

10/09/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5618 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Cross. A

PCT/US 02/03543

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 209 441 A (SATO TOMOAKI) 11 May 1993 (1993-05-11) figure 1 -----	1,2,4,5

Information on patent family members

PCT/US 02/03543

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 29911639	U	23-09-1999	JP 2000018433 A	18-01-2000
			DE 29911639 U1	23-09-1999
			US 6241198 B1	05-06-2001
EP 0569297	A	10-11-1993	FR 2690970 A1	12-11-1993
			DE 69303229 D1	25-07-1996
			DE 69303229 T2	30-01-1997
			EP 0569297 A1	10-11-1993
			ES 2089752 T3	01-10-1996
EP 0666628	A	09-08-1995	DE 9401393 U1	19-05-1994
			CA 2140941 A1	28-07-1995
			DE 69509933 D1	08-07-1999
			DE 69509933 T2	09-12-1999
			EP 0666628 A1	09-08-1995
			ES 2132524 T3	16-08-1999
			JP 7310866 A	28-11-1995
			US 5588683 A	31-12-1996
US 5209441	A	11-05-1993	NONE	